

UHAND SILAGE RECLAIMER



SILAGE RECLAIMER - SR SERIES

Model		SR-5	SR-6
Overall Dimensions (L×W×H)	mm	5800×1600×3350	5800×1600×3350
Total Weight	kg	2000	2100
Reclaiming Height	m	5	6
Power (Reclaiming Head)	kW	7.5	7.5
Conveyance Type		Chain-Scraper Type	Chain-Scraper Type
Hydraulic Motor Power	kW	5.5	5.5
Hydraulic Motors		BM5-400 / BM5-250	BM5-400 / BM5-250
Hydraulic Cylinder		1480	1740
Blade Quantity	pcs	88	88
Reclaiming Efficiency	t/h	24	28
Travel Speed	km/h	1.75	1.75
Front Tires		550/16×2	550/16×2
Rear Tires		650/16×2	650/16×2
Control Mode		Hydraulic & Electric Button	Hydraulic & Electric Button

The Silage Reclaimer is compatible with various silage bunkers and pits, specifically designed for mechanized silage retrieval and transfer.

Efficient Material Retrieval: The front-mounted reclaimer attachment smoothly scrapes silage from the bunker, reducing waste caused by compaction or clumping.

Labor-Saving Conveying: The inclined conveyor transfers the silage directly to feed wagons or feeding equipment, eliminating the need for manual handling.

Flexible Operation: The wheeled design allows easy movement between sites, and the simple electric control panel makes operation intuitive. It adapts to the feeding rhythm of farms of all sizes.

With the Silage Reclaimer, farms can improve silage feeding efficiency while significantly reducing labor costs.

*Product images & specs are for illustrative purposes only. Minor variations (due to production batches or upgrades) may occur, with no impact on core functions. Actual product shall prevail. For inquiries, contact our sales team.



Hydraulic Power Unit (HPU)



Hydraulic Control System



Reclaiming Drum



Three-Phase Asynchronous Motor